

XELYTE®



SECURE
— AND STRONG

XELYTE®

A STRONG AND SECURE RAILING

RECTANGULAR RAIL AND SQUARE BARS

-  Military sites
-  Logistics hubs
-  Sensitive industries

R A I L I N G S



Double rail

Strong points

Strength

- Tamper-proof
- High strength profiles:
 - Rectangular rail 50x30 mm
 - 25x25 mm square bars inclined at 45°
- Linking pieces clamped together in the factory
- Optional double rail for extra security

Long life

- Finish: galvanised steel + polyester coating
- Ten years Professional guarantee



To benefit from the DIRICKX 10 years Professional Guarantee against corrosion, please ask us for our "request for guarantee" document. The Guarantee is provided in accordance with the general conditions governing attribution.

■ Attractive

- Design: uniquely shaped post with factory assembled solid cap the same colour as the railing
- Finish: linking system painted the same colour as the railing
- Standard colours: ● Green 6005 - ● Black 9005 - ● White 9010

■ Easy to install

- Sequential installation
- Post slotted throughout its height (every 5 cm)
- Any configuration possible:

- Corners



- Steps



- Railing can be cut down and repaired using standard elements

■ Modular

- Wide range:
 - 7 railing heights: from 1 m to 2.50 m
 - Post on base plate or to be embedded: from 1 m to 2.50 m
- Options:
 - Bars extending from top rail and/or bottom rail
 - Flush finish at top rail and/or bottom rail
 - Tops of bars cut off at 45° (standard)
 - Tops of bars cut straight across (option)



Post on base plate



Bars extending from rail
Cut off at 45°




Flush finish at top rail



Bars extending from rail
Cut straight across

■ Accessories:

- Wall fixing: to be embedded or on base plate
- Accessory for concrete gravel board



- 200 RAL colours



TECHNICAL SPECIFICATION

XELYTE®

How to install



Each order is delivered with instruction leaflet



1 Install the first post

2 Position 2 lugs in the post

3 Offer the railing to the post

4 Lock the railing onto the post using a pin



Technical specification XELYTE®

XELYTE	RAILING						POST TO BE EMBEDDED		POST ON BASE PLATE	
Nominal height (m)	Post centres (m)	Rail (mm)	Bars (mm)	Bars extending above top rail	Bars extending below bottom rail	Weight (Kg)	Nominal height (m)	Weight (Kg)	Nominal height (m)	Weight (Kg)
1.00	2.469	50 x 30	25 x 25	no	no	38	1.50	5.50	1.00	6.50
1.20	2.469	50 x 30	25 x 25	no	no	42	1.70	6.50	1.20	7.50
1.50	2.469	50 x 30	25 x 25	yes	yes	49	2.00	8.00	1.50	9.00
1.80	2.469	50 x 30	25 x 25	yes	yes	56	2.30	9.50	1.80	10.50
2.00	2.469	50 x 30	25 x 25	yes	yes	60	2.50	10.50	2.00	11.50
2.20	2.469	50 x 30	25 x 25	yes	yes	65	2.70	12.00	2.20	13.00
2.50	2.469	50 x 30	25 x 25	yes	yes	72	3.00	13.00	2.50	14.00



DIRICKX GROUPE - 53800 CONGRIER - FRANCE
TÉL : 00 33 (0)2 43 09 38 38 - FAX : 00 33 (0)2 43 09 38 99
www.dirickx.com - E-mail : info@dirickx.com